

How To Install Security Film

Safe Lockdowns Security Film (SLSF) installs on the door glass and allows the room to be viewed from the hallway when the lights in the room are on, but becomes reflective, like a mirror, on the hallway side of the door when the lights in the room are turned off. This eliminates the need for the teacher to cover the door windows.

With **Safe Lockdowns Security Film** and **our patented** anti-latch devices installed on your doors, locking down the classroom in seconds becomes as simple as 1,2,3...

1. Switch School Safe to the lockdown position.
2. Switch the lights off.
3. Direct the students to the safe area of the classroom.

No need to cover the door window as the School Safe Security Film turns the window into a two-way mirror allowing the teacher to see out but an intruder would see their own reflection.

School Safe Security Film comes in pre-cut sizes or can be custom cut to your specifications.

Tools Needed:

- Window Cleaning Solution (Windex)
- Spray bottle of water and a few drops of dish washing detergent or baby shampoo, the "Application Solution"
- Tape – Clear or Duct
- Squeegee – for smoothing film
- Utility knife – for trimming excess film from edges
- Edging tool – or ruler to ensure a clean edge
- Low Lint cloth – for cleaning film and glass

How To Install Security Film

1. Apply the window film to the inside of the window.
2. Clean window; Generously spray window and use razor blade to remove stubborn dirt or paint. Use squeegee downward and wipe off dirt from edges.
3. Identify Clear Liner; Place the film on a clean, flat surface. Select one corner of the film and attach two small pieces of tape (3-4inches) to each side of film. Leave some tape hanging over the corner. Press the two pieces of tape firmly together, then quickly pull them apart to begin separating the clear liner away from the adhesive side of the film. Do not totally separate the liner at this time but leave the tape in place and move to the next step.
4. Wet the window with the Application Solution
5. Remove Clear Liner; Begin to peel the two strips of tape apart to release the liner from the film. As you begin to pull off the liner, spray the exposed adhesive side of the film with the Application Solution until the clear liner is removed and the adhesive side is completely saturated. Try to keep the film from touching itself.
6. Apply film to glass; Hold film up to glass and apply. Use your hands to smooth the film out and position it so the excess is overlapping the edges of the window.
7. Spray the entire surface of the film facing you with the Application Solution. Lightly squeegee the center section of the film from the top to the bottom to set the film in place. Begin to smooth the film, starting at the top of the window. Squeegee from the center to the right side and work downward leaving excess film around the edges. Repeat for left side.
8. Trim film; Place a ruler or straight edge along the edge of the window and film. Line the knife and edging tool up to a top corner of the window. Slowly and firmly, pull the knife and straight edge down to trim the excess film. Gently pull the trimmed film away from the window. Repeat this process on all four edges of the film.
9. Squeegee dry; Re-wet the film and squeegee from the center to the right side, working from the top down. Repeat this process for the left side. Press firmly to remove all the water. If air bubbles are present squeegee them out to the edges.